

# GraphLine Inc.<sup>®</sup>

1100 International Pkwy.  
Suite 100 Sunrise FL 33323  
800-998-3200

## MATERIAL SAFETY DATA SHEET

IN CASE OF TRANSPORTATION EMERGENCY (Spill, Leak, Fire, Exposure, Accident)  
Call CHEMTREC 1-800-424-9300 (24 Hour)

### SECTION 1: IDENTIFICATION

**Name:** SOBI WATERLESS S KR Process Color

**Revision** 4/2/2009

**Product Number** INC45319

**Size** 1K can

**Formula** Pigment / Synthetic resin

### SECTION 2: COMPOSITION / INFORMATION ON INGREDIENTS

<u>C.A.S. #</u>	<u>INGREDIENTS</u>	<u>%</u>
8042-47-5	Petroleum Solvent	15- 30
PIGM	PIGMENT	5- 25
RESI	Resin	30- 40
Veg Oil	Vegetable Oil	20- 30

<u>EXPOSURE LIMITS</u>	<u>OSHA</u>		<u>ACGIH</u>		<u>CANADA</u>	
	<u>TWA</u>	<u>STEL</u>	<u>TWA</u>	<u>STEL</u>	<u>TWA</u>	<u>STEL</u>
Petroleum Solvent	None	None	None	None	None	None
PIGMENT	NONE	NONE				
Resin	NONE	NONE				
Vegetable Oil	None	None	None	None	None	None

#### Source of Exposure Limit Data:

OSHA: Occupational Safety and Health Administration

ACGIH: American Conference of Governmental Industrial Hygienists

CANADA: Province of Alberta's Occupational and Health and Safety Act.

### ADDITIONAL EXPOSURE INFORMATION

<u>CAS. NUMBER</u>	<u>SKIN DESIGNATION *</u>			<u>CARCINOGENS</u>			<u>PRIMARY HAZARD</u>	<u>IDLH (ppm)</u>
	<u>OSHA</u>	<u>ACGIH</u>	<u>CANADA</u>	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>		
8042-47-5	No	No	No	No	No	No		Unknown
PIGM	No	No	No					
RESI	No	No	No					
Veg Oil	No	No	No	No	No	No		Unknown

\* For substances designated as a 'Skin' hazard, protective measures are recommended to prevent or reduce skin absorption. These measures may include the use of gloves, aprons, goggles or other equipment, as well as engineering controls or work practices.

### SECTION 3: HAZARDS IDENTIFICATION

#### EYES CONTACT:

Avoid eye contact. This product may be slightly irritating to the eyes upon direct contact.

#### SKIN CONTACT:

Avoid skin contact. This product is not irritating to the skin upon direct contact. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping and reddening. This condition may make the skin more susceptible to other irritants and disease. Pre existing skin conditions may make the skin more susceptible and facilitate uptake by this route.

#### INHALATION:

Caution should be taken to prevent aerosolization or misting of this product. Acute overexposure may result in irritation of the throat and lungs.

**INGESTION:**

Do not ingest.

**H.M.I.S. CODES:****HEALTH:****FIRE:****REACTIVITY:****PROTECTION:****SECTION 4: FIRST AID MEASURES****EYE CONTACT:**

Immediately flush eyes with plenty of low pressure water and continue flushing for 15 minutes until irritation subsides. Seek medical attention.

**SKIN CONTACT:**

Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention.

**INHALATION:**

If mist is generated when the material is heated or handled, remove victim from exposure. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen, if it is available. If victim is unconscious, remove to fresh air and seek medical attention.

**INGESTION:**

Do not ingest.

**SECTION 5: FIRE FIGHTING MEASURES****Flash point (F) :** 284**FLAMMABILITY LEL-****UEL-****Extinguishing media:** Use water fog, foam, CO2 or dry chemical extinguish media.**Special fire fighting procedures :**

Remove all ignition sources. Wear self contained breathing apparatus and protective equipment when entering confined areas. Move container from fire area, if it can be done without risk. Use water spray to cool nearby containers and structures exposed to fire.

**Unusual fire and explosion hazards :**

Dense smoke may be generated while burning, carbon dioxide, carbon monoxide and other oxides may be generated as products of combustion.

**NATIONAL FIRE PROTECTION ASSOC. CODES****HEALTH:****FIRE:****REACTIVITY:****SPECIAL:****SECTION 6: ACCIDENTAL RELEASE MEASURES****SPILL RESPONSE:**

Wear self contained breathing apparatus and full protective clothing. Eliminate ignition sources. Avoid eye or skin contact. Place leaking containers in well ventilated area. If fire potential exists, blanket spill with foam or use water spray to disperse vapors. Contain spill to minimize contaminated area and facilitate salvage or disposal. To clean up spill, flush area sparingly with water or use an absorbent. Avoid runoff into storm sewers and ditches which lead to natural waterways. All clean up and disposal should be carried out in accordance with federal, state and local regulations. If required, federal, state and local authorities should be notified.

**SECTION 7: HANDLING AND STORAGE**

Store indoor at normal temperature. Avoid direct sunshine.

**SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Eye protection: Chemical splash goggles. Protective gloves: neoprene. Ventilation: Local exhaust recommended. For routine operations, an impervious apron and gloves are recommended.



The data in this Material Safety Data form relates to the specific material designated herein and to the standard use of same in combination with other materials or processes. The hazards covered are believed to be those most likely to occur in the reasonable, contemplated, or ordinary use of these chemicals. No warranty is made or implied in respect of other hazards which may occur as a result of unreasonable, abnormal, or unusual usage, or non-standard application of these materials. The information accumulated herein is believed to be accurate, but GraphLine Inc. expressly denies any warranty to such effect. Customers or recipients are advised to confirm, in advance that the information is current, applicable and suitable to their circumstances. This information is furnished as a service only.